



PO Box 10  
Kanawha, IA 50447

888-254-3337  
www.kiefermfg.com

## A2G Deluxe II Gooseneck 7'x6'6"x24'

### Standard Features:

- All Wheel Electric Brakes
- Aluminum Extruded Fenders
- Aluminum Extruded Interlocking Floor with Traction Ribs and Integrated Cross-members
- Center Divider Gate w/Walk-thru Gate w/Sam Latch
- DOT Approved Lighting
- Enclosed Wiring
- Escape Door (drivers side)
- LED Lighting: All Exterior Marker & Stop/Turn/Tail
- Lights: Rubber Mounted - Sealed in Rear Frame
- Radial Tires on Silver Modular Wheels w/Stainless Steel Centers
- Rear Gate: Full-Swing 1/2 Slide w/2" Rubber Rollers and Nylon Pads w/ Slam Latch
- Heavy-Duty Rubber Bumper
- Side Uprights 1"x3" Aluminum Tubes 16" to 21" On Center
- Square Tube Rear Frame: 4"x4" Exclusive Design
- Standard Height: 6' 6"
- Torsion Axles
- Tapered Nose: 5' Width
- Air Flow Openings: (2) at Top of Trailer Sidewall (#2 Sides)

**Your Local Kiefer Dealer**



*A2G Deluxe II: 7'x6'6"x24'*

### Benefits:

Aluminum Interlocking Flooring with Integrated Cross-member every 4-1/2 inches  
Simply the strongest Floor available

Double headers over every interior Gate:  
More Center Gate support and longer Gate life.

4" x 4" Square Tube Superstructure:  
Strong Rear Door Frame with Large Cast Corners that disperse Stress away from Corners.

Side Uprights Extending Past the Floor:  
Trailer is not reliant on welds only at Floor Joint for Wall Strength.

Quick Slam Latches:  
Quick close feature allows you to close Doors and Gates quickly and alleviate the worry of Livestock getting past the Gates.

And More...Check One out Today!

# Kiefer Built

## Deluxe II Gooseneck - Side View Model - 7' x 6" 6" x 24'

July 31, 2011 dta  
Kiefer Manufacturing reserves the right to change  
or alter these specifications without notice.  
Dimensions are approximate and may vary.

