



PO Box 10
Kanawha, IA 50447

888-254-3337
www.kiefermfg.com

Stockman Pull-Type & Gooseneck Trailers

Kiefer Stockman Steel Livestock Trailers are built stronger to last longer.

Kiefer Stockman Livestock trailers feature a one piece 4" x 4" formed radius rear superstructure, eliminating corner welding around the rear opening where most other trailers fail. This method of manufacturing is also utilized for center and rear gates, providing strength and prolonging service.

Quality DuPont® Imron 5000 Paint and DuPont® Corlar Primer provide an automotive-grade, long-lasting finish.

Once you compare Kiefer Stockman to more traditional steel trailer construction, you will see why it has become the first choice for many satisfied customers. Check out our website and find your Stockman at a dealer near you!

Your Local Kiefer Built Dealer



Note: Some Optional Items Shown in photos.

August 1st, 2011

2012 Model Year



Contact your local Kiefer dealer for
your next trailer purchase.

Stockman Trailers



Shown with optional High Impact Plastic & Flip Vents

Standard Equipment:

- All Wheel Electric Brakes
- Brake Away Battery & Switch
- Body Width, 6 foot 8 inches
- Coupler 2 5/16"
- Escape Door (passenger side)
- Frame Cross-members 2" x 3" x 1/4"
- Rubber Gravel Guard
- DOT Approved Lighting
- Enclosed Wiring
- LED Lighting Marker & Stop/Turn/Tail
- Stall Height 78 inches
- Front Wrap Sheet 16 Ga.
- Torsion Axles
- Rear Frame 4" x 4" Square Tube (11Ga.)
- Roof Sheeting 18 Ga.
- Rubber Bumper
- Safety Chains (2)
- Side Sheet 48" (16 Ga.)
- Tube Uprights Stakes (14 Ga.) 1 " x 2"
- Wheels Silver Modular

Kiefer Manufacturing reserves the right to change or alter these specifications without notice. Dimensions shown are approximate and may vary. Some trailers shown with optional equipment. See a Kiefer dealer for current specifications and optional equipment listings.